

# FORTEBRACCIO

design Alberto Meda / Paolo Rizzatto, 1998



Type: Wall or ceiling/wall

Light source:	D33Nsp.60	28W Spot R50 E14 42W HSGSA E14 LED E14	EEL: A EEL: D EEL: A++/A+/A
	D33Nsp.100	42W Spot R63 E27 70W HSGSA E27 LED filament E27	EEL: A EEL: D EEL: A++/A+/A
	D33N.100	70W HSGSA E27 LED filament E27	EEL: D EEL: A++/A+/A

Product use: Indoor

Materials: Injection-moulded grip /moulded polycarbonate sheared and formed steel arms, die-cast metal joints

Colors: White, black soft touch, metal

Description: The central joint allows the two arms to rotate independently on the horizontal and vertical axis, guaranteeing great fluidity of movement even in extreme and unusual positioning. The polycarbonate grip enables users to maneuver the lamp simply and manageably.

Insulation class:

Awards: Compasso d'Oro ADI 2001, selection

Reference code:	Structure	
	D33N.100	1D33N2GI0002 white 1D33N2GI0001 black soft touch 1D33N2GI00AA metal
	D33Nsp. 60	1D33NSPI0002 white 1D33NSPI00AA metal 1D33NSPI0001 black soft touch
	D33Nsp. 100	1D33NSGI0002 white 1D33NSGI00AA metal 1D33NSGI0001 black soft touch
	Component	
	D33N/3	1D33N/03000A universal joint metal

